

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 December 2000 (07.12.2000)

PCT

(10) International Publication Number
WO 00/72797 A1

(51) International Patent Classification⁷: **A61H 15/00**

(21) International Application Number: **PCT/US00/13484**

(22) International Filing Date: **16 May 2000 (16.05.2000)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
60/136,549 28 May 1999 (28.05.1999) US
09/412,819 5 October 1999 (05.10.1999) US

(71) Applicant and

(72) Inventor: **MORRIS, John, K.** [US/US]; 3125 Hunting
Valley, Ann Arbor, MI 48104 (US).

(72) Inventor: **COLESTOCK, Harry, E.**; 6449 Hellner Road,
Ann Arbor, MI 48104 (US).

(74) Agents: **POSA, John, G. et al.**; Gifford, Krass, Groh,
Sprinkle, Anderson & Citkowski, PC, Suite 400, 280 N.
Old Woodward Avenue, Birmingham, MI 48009 (US).

(81) Designated States (*national*): AL, AM, AT, AU, AZ, BA,
BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES,
FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP,
KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN,
MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent
(AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,
MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **PORTABLE, SELF-CONTAINED APPARATUS FOR DEEP VEIN THROMBOSIS (DVT) PROPHYLAXIS**



(57) Abstract: An entirely self-contained, patient-worn apparatus for deep vein thrombosis (DVT) prophylaxis, and other conditions includes an inflatable/deflatable bladder (102) disposed against an extremity such as the upper calf (109), foot, or hand of a patient, or within a cast. An inelastic member (106, 108) is preferably used to fully enclose the bladder and body part, such that compressive forces are directed substantially entirely against the body part of the patient when the bladder (102) expands, thereby conserving the power and reducing the volume of pneumatic compression required to operate the device. Given this conservation of energy, the invention may be battery operated from a source immediately proximate to the bladder arrangement, enabling the entire device to be self-contained and, in fact, worn by the patient. The reduced volume also allows the use of miniaturized components including the compressor motor and compressor.

WO 00/72797 A1

PORTABLE, SELF-CONTAINED APPARATUS FOR DEEP VEIN THROMBOSIS (DVT) PROPHYLAXIS

Field of the Invention

This invention relates generally to body massaging appliances and, more particularly, to a portable, self-contained apparatus for deep vein thrombosis prophylaxis.

5

Background of the Invention

Persons undergoing surgery, anesthesia and extended periods of bed rest or other inactivity are often susceptible to a condition known as deep vein thrombosis, or DVT, which is a clotting of venous blood in the lower
10 extremities and/or pelvis. This clotting occurs due to the absence of muscular activity in the lower extremities required to pump the venous blood (stasis), local vascular injury or a hypercoagulable state. The condition can be life-threatening if a blood clot migrates to the lung,
15 resulting in a "pulmonary embolus" or otherwise interferes with cardiovascular circulation.

It is known that this condition may be controlled or alleviated by applying intermittent pressure to a patient's legs to assist in blood circulation (venous return). Many
20 devices have been proposed, including compression boots and other inflation tube devices, but heretofore all of the proposed solutions have been complex, or bulky, or both, and in each case, certainly not portable and self-contained.

25

One reason why currently available devices are large

- 2 -

and complex is due to the fact that the precise level of pulsatile activity required to manage the condition is largely unknown. Commercial devices may therefore provide a more complex massaging action than is necessary. As a result, many existing devices include a plurality of inflatable chambers, spaced at intervals along the leg of a patient, with complex sequencing means being used to provide a vertical pumping action to direct blood flow through the leg and into the torso. Apart from the fact that such sophistication may be unnecessary in many cases, the use of a complex sequential pumping operation requires the use of a heavy and expensive drive unit, precluding portability. Devices of this type are described in U.S. Patent Nos. 4,013,069; 4,453,538; 4,702,232; 4,841,956; 4,941,458; 5,014,681; 5,263,473; and 5,674,262, and elsewhere.

Although less complex inflation devices have been disclosed, the descriptions rely upon conventional non-portable compressed-air sources. A case in point is U.S. Patent No. 4,153,050, which describes a DVT stocking used in conjunction with a fillable bladder having only a few chambers. The result is a less complex structure, however, even in this case, the bladders are interconnected to a remote air supply through an interconnecting conduit. No mention is made of true device self-containment and portability.

The need therefore remains, for a portable, self-contained, preferably wearable, device to prevent DVT and

like venous conditions. Such a device would also improve upon current devices which, being cumbersome in nature, lead to poor compliance on the part of the user, and are accordingly less effective. Additionally, existing
5 devices, which must be tethered to pneumatic control units, are difficult to apply to the same extremity associated with a particular surgical procedure. For example, it is difficult to apply existing devices to the leg associated with same side hip surgery due to the required
10 interconnections.

Summary of the Invention

The subject invention improves upon the prior-art by providing an entirely self-contained, patient-worn apparatus for deep vein thrombosis (DVT) prophylaxis, and
15 related conditions. According to a preferred embodiment, an inflatable/deflatable bladder is disposed against an extremity such as the upper calf, foot or within a cast. To treat edema, an inflatable/deflatable bladder may be disposed against at least a portion of the hand. A
20 generally inelastic member is preferably used to fully enclose the bladder and associated body part, such that compressive forces are directed substantially entirely against the body part of the patient when the bladder expands, thereby conserving the power and reducing the
25 volume of pneumatic compression required to operate the device. Given this conservation of energy, the invention may be battery operated from a source immediately proximate

to the bladder arrangement, enabling the entire device to be self-contained and, in fact, worn by the patient. The reduced volume also allows the use of miniaturized components including the compressor motor and compressor.

5 The miniature pump is preferably capable of inflating the bladder to a desired level of pressure so as to augment venous return. A valve may be provided as a pressure release mechanism or, preferably, a natural bleeding of the system is relied upon for decompression following an
10 inflation cycle. The electronics used to drive the compressor, which may be of the type used in commercial blood-pressure measurement cuffs, may be very simple, including a solid-state timer coupled to a relay or other appropriate switching means.

15 A distinct advantage of the invention is that the device may be worn at all times, including the limb being operated upon during surgery. In an alternative embodiment, to further increase battery life, a sensor may be provided to detect movement of the limb (from which
20 muscle contractions may be implied), such that, should the patient be walking or otherwise active, the pumping action is terminated. One or more mercury switches or other appropriate movement sensors may be utilized for such purpose.

25 The inventive apparatus may additionally be programmed to decrease the rate of inflation/ deflation as a function of time, since it is known that the patient is most vulnerable during and immediately after surgery. Thus, the

inventive apparatus may automatically be programmed to facilitate a relatively high inflation/ deflation rate during a surgical procedure, but then taper off to a more infrequent cycling as a function of time.

5

Brief Description of the Drawings

FIGURE 1 is a drawing which illustrates an embodiment of the invention including a substantially rigid outer shell operative to direct compressive forces into the upper calf region;

10

FIGURE 2 is a drawing which illustrates major components associated with operating a device according to the invention;

FIGURE 3 is a schematic diagram which illustrates preferred electrical circuitry associated with operating the device of Figure 2;

15

FIGURE 4A is a diagram which shows a typical cycling between compression and non-compression according to the invention;

FIGURE 4B is a drawing which shows how the frequency of compression/decompression may fall off as a function of time;

20

FIGURE 5 is a simplified drawing of a foot-worn alternative embodiment of the invention;

FIGURE 6 is a drawing of yet a different alternative of the invention wherein a bladder is introduced in a cast, in this case a leg cast;

25

FIGURE 7A is yet a further alternative embodiment of

the invention wherein a portable inflatable/deflatable bladder is associated with a glove to treat conditions such as edema;

FIGURE 7B is a drawing of a hand-applied embodiment of the invention wherein a larger bladder is placed on the back surface of the hand and;

FIGURE 7C illustrates how apertures may be provided to the glove or other embodiments of the invention, thereby permitting a breathable fabric while still being sufficiently inelastic to provide a requisite level of compression.

Detailed Description of the Invention

Now making reference to the drawings, Figure 1 illustrates a preferred assembly according to the invention for placement relative to the upper calf of a human wearer. Upon reading this specification, it will be apparent to one of skill in the art that the depicted structure may be applied to other areas of the body through appropriate physical modification.

In the preferred embodiment, a simple, single-chambered bladder 102 is disposed between a substantially inelastic outer shell and a compressible portion of the extremity, as against the calf muscle 109, as shown. In the depicted embodiment the inelastic outer shell is composed of rigid anterior and posterior shell components 106 and 108, respectively, which are held in position using hook-and-loop straps 110. As an alternative to one or more

rigid components, an inelastic fabric may alternatively be employed as the shell material.

In any case, in the preferred embodiment the outer shell circumferentially encases the entire extremity, so that a minimum degree of bladder inflation achieves a desired level of compression, thereby conserving battery power. The bladder interconnects to a pressurization unit 120 through an air path 122. The pressurization unit 120 is preferably mounted with respect to an outer surface of the inelastic shell, resulting in an appliance which is entirely self-contained and portable.

Components which make up the electrical and pneumatic circuitry of the invention are depicted in Figure 2. These components include the bladder 102 and an electric motor/compressor 204, which can be a very small device. The system further includes a pressure sensor 206, and an optional pressure relief valve 207 which may be used with, or in place of, a passively controlled leak. A coupling 208 places the bladder, compressor and pressure sensor/switch in pneumatic communication with one another. Electrical wiring 210 interfaces to electronic circuitry best seen in Figure 3. Two user controls 214 are preferably provided, one being an ON/OFF switch and the other being a knob to control frequency of inflation.

As shown in Figure 3, a variable delay based on a 555 timer is used to drive a relay CR1. The relay CR1 uses two sets of contacts -- one normally opened and another which is normally closed. The normally open set of contacts is

in parallel with the pressure switch to minimize chatter, while the other set of contacts is used to turn the compressor on and off. There are two batteries in this configuration. One is a 9-volt battery used to power the electronics, and the other is a 3-volt battery dedicated to the compressor motor. The circuitry has been adjusted so that the batteries last at least a week. In terms of duty cycle, a 5-Megohm potentiometer may be used to vary the inflation/deflation rate from once every minute to once every several minutes. Other repetition rates are possible through appropriate modification to the timing components.

In operation, the compressor is activated to inflate the bladder to achieve a pressure sufficient to augment venous return. For example, it has been determined that a pressure on the order of 50 mm/Hg is adequate, though clearly the invention is not limited in this regard, and maximum pressure may be adjustable through appropriate component adjustment or modification. Deflation of the bladder may either be effectuated through a reliance on system leakage, or a controlled leak valve such as item 207 in Figure 2 may be added for a faster, more precise rate of deflation. The pressure may also be "held" for a predetermined period of time, as desired, until the onset of deflation.

Figure 4A should help to illustrate the operation of the apparatus according to a preferred method. At time 350, the unit is activated using the ON/OFF switch, with frequency being adjusted using the potentiometer shown in

Figure 3 as discussed above. During time period 351, the compressor is operative to inflate the bladder until the pressure switch detects a desired maximum pressurization, at which point the pressure switch closes at time period 5 352. This starts a time delay 354 wherein the relay CR1 is energized at the initiation of the delay period. In the event that an active pressure release valve is used, the valve is also energized to release pressure between cycles during the delay period 354.

10 At the termination of the delay period 354, the time delay relay CR1 drops out at 356, commencing another pressurization cycle with the compressor being energized during period 358, and so on. The cycles continue in this fashion until the ON/OFF switch is turned off.

15 With additional electronic sophistication, the level of compression, time delay of decompression, or the cycling between compression and decompression may individually or together be varied as a function of time to facilitate a particular treatment regime, or to save on battery power, or both. As shown in Figure 4B, for example, the system 20 may operate according to a manual mode during a surgical procedure, for example, wherein the cycling between compression and decompression is relatively high. In the chart of Figure 4B, a figure of one cycle per minute has 25 been chosen, though such a value is clearly exemplary and may be varied in accordance with component adjustment.

The system may operate during this manual mode during surgery along plateau 360, offering a relatively high

cycling rate between compression and decompression. At time 362, a user input (not shown) may be activated to place the system into an automatic mode whereby the cycling rate slowly drops off during the hours and days following surgery, so that in several days' time, the rate may reduce to one cycle every ten minutes at time 366, and even up to one cycle every hour or longer, as the case may be. It will be readily appreciated to one of skill in the art of circuit design, that, in order to accommodate these changes to the operation, the timer shown in Figure 3 may be replaced with a microcomputer or custom processor, with appropriate software programs and user inputs to carry out the actions just described.

One advantage achieved through portability is that, at least with respect to total hip arthroplasty, the inventive device may be placed on the leg being operated upon. An additional advantage gained through self-contained portability is increased patient compliance. Current devices are cumbersome, often requiring nursing assistance to connect and disconnect tubing running from the compressor unit to the stockings. This results in many "unprotected" periods of time and thus decreased effectiveness. The convenience of this device will not require that it be disconnected to use the bathroom, for example. This is in contrast to existing devices which generally must be placed on the opposite leg until after the procedure. Although this arrangement provides a certain beneficial effect, a greater benefit is gained

through positioning on the same extremity as that being operated upon.

To further increase battery life, and to enable a patient to wear the device at all times, in an alternative
5 embodiment, a sensor is provided to detect movement of the limb, such that should the patient be walking or otherwise active, the pumping action is terminated to conserve battery power. A mercury switch or other simple sensor is preferably utilized for such purpose.

10 The invention is not limited to leg application, and may be applied to any extremity, depending on the condition to be treated or prevented. For example, Figure 5 illustrates an alternative embodiment of the invention, wherein a bladder 401 is held against the bottom of the
15 foot of a wearer 404 through the use of a shoe-like structure 410. The portable compressor unit 412 may be conveniently located on top of the foot as shown, with a pneumatic line 414 interconnecting the unit 412 to the bladder 402. Velcro straps 420 may be provided to don and
20 remove the appliance. Although the bladder 402 is shown directly under the foot, placement may be altered to the side or even top of the foot, depending on the way the inelastic material comprising the device is precisely arranged.

25 The invention is also applicable to existing casts, as shown in Figure 6. In this case, a bladder 502 interconnected to a portable compressor unit 504 through a short pneumatic tube 506 would be placed against the leg

- 12 -

and preferably taped into place. Although the bladder 502 is shown on the back of the leg, it may also be positioned against the side of the calf, on the other side of the leg, or even in front, due to the inventive use of an inelastic
5 outer shell. After this procedure, the cast would be applied to the leg or other appendage as normally done, with, perhaps, the final windings of the cast being used to hold the compressor unit 504 into place.

Figures 7A-7C illustrate ways in which the invention
10 may be applied to the hand, in this case more to treat conditions such as edema, as opposed to DVT. In Figure 7A, for example, a portable compressor unit 602 is mounted onto the top of a "glove-within-a-glove" structure 604 which may, or may not, have finger openings 606. Pneumatic
15 tubing 610 from the portable compressor unit 602 extends to the outer glove through connections to one or more of the fingers, for example, with the inflation and deflation thereof being controlled in accordance with the condition to be treated or avoided.

20 Figure 7B illustrates an alternative embodiment wherein a bladder 620 covers the entire back of the hand, thereby providing compression against a larger area. Again, however, the portable compressor unit 622 would be mounted or otherwise laminated to a glove structure 624
25 with tubing 630 interconnecting the unit to the bladder 620. As shown in Figure 7C, perforations or larger apertures 640 may be provided in between the areas containing the bladder(s), thereby rendering a breathable

nature to the fabric to avoid over-moistening of the skin, and rashes and other conditions which might result. So long as the remaining structure of the fabric used for the appliance is otherwise inelastic, holes or apertures 640 would not interfere with the low-power operation of the invention as described herein.

Thus, what has been described is a portable compression/decompression device which may be applied to various areas of the body to prevent conditions such as 10 deep vein thrombosis, and to treat edema and like ailments. In contrast to existing devices, the invention is entirely self-contained, enabling all of the necessary components to be carried/worn by a user with the goal being higher compliance and greater effectiveness. Various embodiments 15 of the invention are also more discrete as compared to existing devices, enabling the wearer to be treated, while in some cases, others do not even realize the inventive devices are in operation. For example, the leg-worn units may be slim enough in profile to be worn under trousers, 20 and the shoe embodiment such as that depicted in Figure 4 may be shaped and colored to look just like a piece of ordinary footwear. Even the glove embodiments associated with Figures 7A and 7C could be made very discrete, and in the form of a normal-looking glove.

We claim:

1. Portable apparatus for deep vein thrombosis (DVT)
2 prophylaxis, comprising:

a substantially inelastic outer shell having an inner
4 wall, the shell being dimensioned for wearing around a
portion of a human extremity having an outer surface;

6 an inflatable/deflatable bladder disposed between the
inner wall of the outer shell and the outer surface of the
8 extremity; and

self-contained, battery-operated electrical and
10 pneumatic circuitry supported proximate the bladder, the
circuitry including an operator control operative to at
12 least inflate the bladder on a regular and periodic basis.

2. The apparatus of claim 1, wherein the circuitry
2 includes:

a miniature air compressor to inflate the bladder; and
4 a pressure sensor in pneumatic communication with the
bladder to terminate the operation of the compressor upon
6 reaching a pressure established through the operator
control.

3. The apparatus of claim 1, wherein the
2 substantially inelastic outer shell is a cast.

4. The apparatus of claim 1, wherein the circuitry
2 further includes means for deflating the bladder upon
achieving a predetermined pressure.

5. The apparatus of claim 4, wherein the means for
2 deflating the bladder upon achieving a predetermined
pressure includes a controlled leak valve/deflation valve.

6. The apparatus of claim 1, wherein the
2 substantially inelastic outer shell is dimensioned for
wearing around an upper portion of a human calf.

7. The apparatus of claim 1, wherein the substantially
2 inelastic outer shell is dimensioned for wearing around a
human foot.

8. The apparatus of claim 1, wherein the substantially
2 inelastic outer shell is dimensioned for wearing around at
least a portion of a human hand.

9. The apparatus of claim 1, wherein the
2 substantially inelastic outer shell is substantially rigid.

10. The apparatus of claim 1, wherein the
2 substantially inelastic outer shell is composed of a non-
stretch fabric.

11. The apparatus of claim 1, further including a
2 sensor for operating the circuitry only when the extremity
has been substantially motionless for a predetermined
4 period of time.

12. Portable apparatus for deep vein thrombosis (DVT)
2 prophylaxis, comprising:

a substantially inelastic outer shell having an inner
4 wall, the shell being dimensioned for wearing around the
upper portion of a human calf;

6 an inflatable/deflatable bladder disposed between the
inner wall of the outer shell and the outer surface of the
8 calf; and

self-contained, battery-operated electrical and
10 pneumatic circuitry supported immediately outside the outer
shell, the circuitry including an operator control operative
12 to at least inflate the bladder on a regular and periodic
basis,

14 the circuitry including:

a miniature compressor operative to fill the
16 bladder with air, and

a pressure sensor operative to turn off the
18 compressor upon reaching a predetermined bladder pressure.

13. The apparatus of claim 12, wherein the inelastic
2 outer shell forms part of a cast.

14. The apparatus of claim 12, wherein the circuitry
2 further includes means for deflating the bladder upon
achieving a predetermined pressure.

15. The apparatus of claim 14, wherein the means for

2 deflating the bladder upon achieving a predetermined pressure includes a controlled leak valve/deflation valve.


16. The apparatus of claim 12, wherein the
2 substantially inelastic outer shell is substantially rigid.


17. The apparatus of claim 12, wherein the
2 substantially inelastic outer shell is composed of a non-stretch fabric.


18. The apparatus of claim 14 wherein the
2 substantially inelastic outer shell is dimensioned for wearing around an upper portion of a human calf.



19. The apparatus of claim 14 wherein the
2 substantially inelastic outer shell is dimensioned for wearing around a human foot.

20. The apparatus of claim 14 wherein the
2 substantially inelastic outer shell is dimensioned for wearing around at least a portion of a human hand.



**Fig - 1**

**Fig - 2**

**Fig - 3**

**Fig - 4A****Fig - 4B**

5/7






Fig - 6

717

Fig - 7B





Fig - 7C



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US00/13484

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A61H 15/ 00

US CL : 601/150, 152

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 601/148-152, 11-14, 84; 128/DIG 20

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5496262 A (JOHNSON, JR. ET AL) 5 MARCH 1996 (05.03.1996) SEE ENTIRE DOCUMENT	1-20
Y	US 4702235 A (HONG) 27 OCTOBER 1987 (27.10.1987) SEE ENTIRE DOCUMENT	1-20
Y	US 5536233 A (KHOURI) 16 JULY 1996 (16.07.1996) SEE ENTIRE DOCUMENT	1-20
Y	US 3908642 A (VINMONT) 30 SEPTEMBER 1975 (30.09.1975) SEE ENTIRE DOCUMENT	3, 6, 7, 12
Y	US 3901221 A (NICHOLSON ET AL.) 26 AUGUST 1975 (26.08.1975) SEE ENTIRE DOCUMENT	8, 20
Y	US 4941458 A (TAHERI) 17 JULY 1990 (17.07.1990) SEE ENTIRE DOCUMENT	10, 17

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	"&" document member of the same patent family

Date of the actual completion of the international search

14 August 2000 (14.08.2000)

Date of mailing of the international search report

22 SEP 2000

Name and mailing address of the ISA/US

Commissioner of Patents and Trademarks

Box PCT

Washington, D.C. 20231

Facsimile No. (703)305-3230

Authorized officer

Danton DeMille

Telephone No. (703) 308-0858